







Clydesdale

MOBILE FIELD SHFITERS

QUALITY WITHOUT COMPROMISE

Clydesdale mobile field shelters combine the renowned build quality of our sectional timber buildings with all the convenience and flexibility of a moveable unit. Dependant on your area, planning permission may not be necessary – offering an immediate solution for your urgent stabling needs.

COMPARE AND EVALUATE


Stables represent a substantial investment, and we strongly recommend customers to compare our buildings first-hand with any other manufacturers being considered.





MOBILE FIELD SHELTERS

	SPECIFICATION
CHASSIS:	Fabricated steel, galvanised in accordance with BS EN ISO 1461. Designed and engineered to allow load dragging over relatively flat and even ground the welded chassis incorporates front and rear fixed skids, with permanent towing collar
SIZE:	Depending on requirements and on towing vehicle
ROOF LIGHTS:	At least one per shelter
HEIGHT TO EAVES:	8'
HEIGHT TO RIDGE:	9'6"
ROOF:	Corrugated, low-condensation black Onduline with 15-year manufacturer warranty (other colours available)
PRIMARY TIMBER TREATMENT:	Protimised, 25-year guarantee
COLOUR/SECONDARY TREATMENT:	Mid Brown Cuprinol timber preservative
TRUSSES:	3" x 2" (75mm x 50mm) Redwood
PURLINS:	4" x 2" (100mm x 50mm) Spruce
FIXINGS:	Galvanised throughout
GUTTERING:	Guttering and downspouts optional
FRAMING*	Planed and eased Redwood 3" x 2" (75mm x 50mm)
CLADDING**	Vertical 6" x 1" (150mm x 25mm) tongue & groove Redwood
KICKING BOARDS***	Sterling board to 4' height
VENTILATION:	Ridge and eaves ventilation



^{**} Our 25mm (nominal) cladding is significantly stronger than the 19mm shiplap cladding typically specified by others.

DELIVERY AND ERECTION

Mobile field shelters can be delivered and erected to most parts of the UK and Europe using our own team of skilled joiner/installers. Delivered-only prices available on request.

FURTHER INFORMATION

Clydesdale manufacture a full range of permanently fixed field shelters, stables and American barns in sizes to suit individual requirements. For further sales, quotations or technical information, please contact our customer service team on 01663 746784 or visit our website at www.clydesdale-timber.co.uk

Clydesdale







^{***} Please note all kicking boards are braced Sterlingboard to 4' (optional to eaves height), we will not install plywood due to the inherent risk of damage to fetlocks in the event of penetration.